



Co2 Carbon Dioxide Fire Extinguishers **(Portable Type)**

Features:

- Simple operation and maintenance
- Exceptionally effective on class B, C and electrical fire
- Manufactured as per BS EN 3-7 standard.
- Portable and compact design
- Cylinder made of special steel to withstand high pressure
- Cylinder are 100% factory tested to 250 bar
- Easy grip valve for comfortable operation
- High grade brass head assembly ensures reliability and optimizes efficiency.
- Unbreakable rising pipe made of aluminum to ensure long lasting life.
- High gloss polyester powder paint stabilized after shot blasting ensures maximum corrosion resistance
- Safety valve is fitted in each extinguisher for maximum safety
- Special hanger for wall mounting
- Labels in Arabic and English Language



Example of class B
Petrol, Oil
Paints, Grease



Example of Class C
Flammable Gases NOT
Having an explosive risk

Specifications:

Model	AC2	AC5	AC6
Extinguisher Capacity	2Kgs	5Kgs	6Kgs
Operating Temperature	+20°C to + 60°C		
Propellant	Self-Propelling		
Working Pressure	55 to 60 Bar		
Test Pressure	250 Bar		
Total Weight	8Kgs	17Kgs	19Kgs
Range of Discharge	4-5m	5-6m	5-6m
Duration of Discharge	7-9sec	11-13sec	13-15sec