



## **Foam (AFFF) Fire Extinguishers** **Portable Stored Pressure Type**

### **Features:**

- Ready for instant use
- Exceptionally effective on class A & B fire
- Manufactured as per BS EN-3 standard.
- Portable and compact design
- Heavy duty steel cylinder
- Made of special CRCA sheet with argon / CO2 welding process
- Simple operation and maintenance
- Cylinder are 100% factory tested to 30 bar
- Easy grip valve for comfortable operation
- Nickel plated brass valve with reliability and long life
- Rugged PVC pick up tube enable smooth flow of the agent.
- Precision built mechanical pressure gauge
- Electrostatic powder painting after shot blasting ensures maximum corrosion resistance
- Internally coated with polyolefin & thermosetting polymer powder using whirl sintering process
- Label in Arabic and English languages



**Example of Class A** Wood  
Paper, Cardboard , Fabric



**Example of class**  
B Petrol, Oil  
Paints, Grease

### **Specifications:**

| <b>Model</b>                 | <b>AFSP1</b>   | <b>AFSP2</b> | <b>AFSP6</b> | <b>AFSP9</b> |
|------------------------------|----------------|--------------|--------------|--------------|
| <b>Extinguisher Capacity</b> | 1ltr           | 2Ltrs        | 6Ltrs        | 9Ltrs        |
| <b>Operating Temperature</b> | +5°C to + 60°C |              |              |              |
| <b>Propellant</b>            | Nitrogen       |              |              |              |
| <b>Working Pressure</b>      | 14 Bar         | 14Bar        | 15Bar        | 15Bar        |
| <b>Test Pressure</b>         | 30 Bar         |              |              |              |
| <b>Total Weight</b>          | 1.8Kg          | 3.7Kg        | 11Kg         | 15.5kg       |
| <b>Range of Discharge</b>    | 2m             | 2m           | 6-8m         | 8-9m         |
| <b>Duration of Discharge</b> | 7-9sec         | 8-12sec      | 16-20sec     | 22-24sec     |