

Dry Powder Fire Extinguishers (Stored Pressure Type)

Features:

- Manufacturing standard BS EN3-7.
- Ready for Instant use.
- Highly effective on Class A, B, C & Electricals Fires.
- Heavy duty steel cylinder
- Made of special CRCA sheet with argon / CO2 welding process
- Simple operation and maintenance
- Cylinders are 100 % factory tested to 30 Bar
- Squeeze grip valve for comfortable operation
- Nickel Plated Brass Valve with reliability and long life
- Rugged PVC pick up tube enables smooth flow of the agent
- Precision built mechanical pressure gauge.
- Electrostatic powder painting after shot blasting ensures maximum corrosion resistance.
- Labels in Arabic and English language.



Example of Class A Wood
Paper, Cardboard , Fabric



**Example of class
B Petrol, Oil
Paints, Grease**



**Example of Class C
Flammable Gases NOT
Having an explosive risk**

Specifications:

| Model No | ADSP1 | ADSP2 | ADSP4 | ADSP6 | ADSP9 |
|-------------------------------|-----------------------------|---------|----------|----------|----------|
| Extinguishers Capacity | 1 Kg | 2 Kg | 4 Kg | 6 Kg | 9 Kg |
| Extinguishing Agent | 40% ABC Dry Chemical Powder | | | | |
| Propellant | Nitrogen | | | | |
| Operating Temperature | -20°C to + 60° C | | | | |
| Working Pressure | 15 Bar | | | | |
| Test Pressure | 30 Bar | | | | |
| Total Weight | 1.8 Kg | 3.7 Kg | 7.5 Kg | 10 Kg | 14 Kg |
| Range of Discharge | 4-5m | 5-7m | 6-8m | 6.-8m | 6-8m |
| Duration of Discharge | 7-9 sec | 8-10sec | 11-13sec | 14-16sec | 16-18sec |