



Other Products

Nozzles



- Type : Jet - spray- shut off nozzle
- Inlet connection : 2 1/2" Male instantaneous as per BS 336
- Material : Aluminium alloy or PVC
- Operating pressure : 150 PSI Max. / 10.5 Kg/cm2
- Finish : Natural

Fire Hose



- UL Listed –
- Size: 2-1/2"
- Working Pressure : 15Bar

4-Way Inlet Breeching



- Body : Cast iron
- Inlet : Four male instantaneous with NRV
- Outlet : 6" NB flanged
- Working Pressure : 150 PSI
- Test Pressure : 325 PSI

2-Way Inlet Breeching



- Body : Cast iron
- Inlet : Four male instantaneous with NRV
- Outlet : 6" NB flanged
- Working Pressure : 150 PSI
- Test Pressure : 325 PSI

Under Ground Hydrant



- Conforming to BS 750
- Body : Cast iron /
- Inlet : Flanged
- Outlet : Gunmetal threaded outlet
- Working pressure : 150 PSI / 10.5 Kg/cm²
- Body test : 325 PSI

Stand Pipes



- Conforming to BS 336
- Body : Aluminium
- Inlet : Threaded BSRT (F)
- Outlet : Female instantaneous as per BS 336
- Working Pressure : 150 PSI / 10.5 Kg/cm²
- Body Test : 325 PSI / 22.5 Kg/cm²